

Key Features:

104 keys
Membrane key with tactile feeling
Key caps laser printed
Auto-repeat function
Ergonomic requirements / standards

Smart Card Interface:

T=0, T=1 protocol support Memory card support through SCM MCARD API Communication speed up to 344,105 bps (PPS, FI parameter) Support ISO 7816 Class A and AB smart card Secure PIN entry via vendor specific IOCTLs

Smart Card Connector:

8 contacts - ISO location Certified for 100,000 insertions Sliding contact



Specification:

Keyboard: 3 LEDs, Num Lock, Scroll Lock, Cap Lock

Smart Card: One dual state green LED Cable: 1.5m long with USB type A connector

Power through USB Bus

Operating Temperature: 0° to 50° Celsius OS: Windows® 98, Me, 2000, XP, CE API: PC/SC, CT-API (thru wrapper on top of PC/SC)

Approval:

- FCC Class B part 15, cULus, CE
- USB
- Microsoft WHQL Me, 2000, XP
- EMV 2000 Level 1

Dimensions: 472(L) * 183(W) * 47.5(H) mm

Hypertec Ltd, 2 Swangate, Charnham Park, Hungerford, Berkshire, RG17 0YX Tel: 0870 243 5603 Fax: 0870 243 5604 www.hypertec.co.uk